



Beam clamp Ø 9mm - without thread

The Rofix beam clamp is extremely suitable for the solid fixing of various suspensions (e.g. sprinkler systems, pipelines, etc.) to a metal beam and this without drilling or welding. The fixing screw is selected in such a way that it prevents the clamp from sliding off the metal beam.



General information

Product ID	50002523
GTIN	5413574113420
Manufacturer name	Rofix
Manufacturer short name	Rofix
Manufacturer product ID	50002523
Brand name	ROFIX
Country of origin	Belgium (BE)
Product in stock	No
Valid from	2000-01-01
Net length	0.18 m
Net width	0.19 m
Net height	0.135 m
Net weight	0.146 kg
Net volume	4.617 m ³
REACH indicator	Does not contain any SVHC in excess of 0.1% product weight
REACH date	2021-09-15
Customs commodity code	73182900

ETIM description

Class	Beam clamp (EC000474)
-------	-----------------------

Group	Mounting systems (EG021005)
Model	Continuous
Horizontal mounting	Yes
Vertical mounting	No
Material	Steel
Material quality	Cast steel
Surface protection	Galvanic/electrolytic zinc plated
Thread type	Metric
Thread size (metric)	9
Thread size connection 2 (metric)	Not applicable
Thread size (imperial)	Not applicable
Thread per inch	Not applicable
Suitable for flange thickness	0..18 [mm]
Bore diameter	9 [mm]
Tube/cable diameter	Not applicable
Breaking load	Not applicable
Permitted work load	1200 [N]

Ordering information

Order unit	Piece
Minimum quantity	50
Quantity interval	50
Content unit	Piece
Content unit quantity	1

Packing information

GTIN	5413574113420
Packing unit code	Carton
Quantity of order units	50
Length	0.18000 m
Width	0.19000 m
Height	0.13500 m
Weight	7.433 kg

Pricing information

Price quantity	1
Price on request	Yes
Price currency	EUR (Euro)
VAT	0.21
Start date	2021-09-15

Attachments

Main product picture	https://files.etim-mapper.com/rofix/Mounting Systems/Strut and Accessories/LR - Rofix - Beam clamp without thread.jpg
----------------------	---

Product categories

Rofix Products	Rail and Accessories Accessories Beam Clamp
----------------	---